



## **FINISHING DETAILS AND MAINTENANCE:**

- General cleaning: It is recommended that you sweep & vacuum the area immediately after installation to remove potential damaging grit and debris.
- Further cleaning with an approved pre-finished floor cleaner is also recommended, as required. Please contact retailer for details.
- Do not buff, wax or use cleaning products that contain surfactants.
- Never steam clean or use a steam mop on the floor.
- Skirtings and scotias: Replace or install new matching skirtings and scotias in all areas. Skirtings are to be nailed into the wall and scotias into the skirtings. DO NOT nail either of these into the AQUALOC flooring.
- Transition pieces: If you have removed any transition pieces and not covered their place with AQUALOC flooring, reinstall them immediately.
- Furniture & appliances: If you are moving and placing furniture and appliances in areas with AQUALOC floors, cover all feet and floor contact points with heavy self-adhesive felt pads to protect the floor. Lift heavy objects when moving (furniture or appliance) DO NOT roll or slide them across the floor.
- We recommend that areas with "rolling loads" (wheelchairs, hospital beds, carts, racks, tables, etc.) should be glued down using a resilient flooring adhesive.
- Felt pads on chair legs should be replaced periodically, as they wear and accumulate grit with use and can damage the floor.
- Outdoor footwear, hard soled shoes and stiletto type heels should not be worn when walking on your AQUALOC floor, as they may mark, abrade or otherwise damage the surface and finish of your floor.